



## **Intelligent Multicriteria Detector**

The Axis-OHX intelligent Multicriteria Detector is a point detection device that continuously samples both the air and the temperature variation in the protected area to provide the earliest warning of a fire condition.

Special algorithms utilise information from both the smoke and heat sensing elements to ensure high level of false alarm rejection without compromising genuine alarm sensing performance.

This detector is characterised by an aesthetically pleasing low profile and is specifically designed for Axis EN control panels.



## **Features**

- Nine modes of operation
- Bi-directional isolator to protect against cable faults
- Utilises Axis EN protocol with high noise rejection
- Dual bi-colour LEDs providing 360° cone of visibility
- Dust Restrict Chamber (DRC) technology offering advanced immunity to airborne contaminants
- Open style mounting base offers easy wiring and low pressure locking
- Addressing and sensitivity settings using the Device Programming Tool or Auto addressing capability via the fire control panel
- Magnet test capability

## Standards & Approvals

- EN 54-5: + A2: Heat Detectors
- EN 54-7: Smoke Detectors
- EN 54-17: Short Circuit Isolators
- CEA 4021: Multisensor Detectors

## **Specification**

| Loop Voltage (*)             | 18-40 V <sub>dc</sub>                |
|------------------------------|--------------------------------------|
| Average Standby Current      | 85 μA @ 24V <sub>dc</sub>            |
| Remote Output Max Current    | 20 mA                                |
| Max number of loop addresses | 240                                  |
| Operating Temperature Range  | -10°C / +55°C                        |
| Humidity (non condensing)    | 95% RH                               |
| Dimensions H x D             | 58 x 100 mm                          |
| IP Rating                    | IP40 (IP42 with silicon base gasket) |

Version [1.00] Page 1 of 2

Weight (Standard Base included)

130 g

(\*) Product operates down to 15 V, but without LED indication.

| Order Codes and Options |                                    |
|-------------------------|------------------------------------|
| Axis-OHX                | Intelligent Multicriteria Detector |
| Axis-MB                 | Base                               |
| Axis-SAMB               | Slave Sounder Base                 |
| Axis-SVAMB              | Slave Sounder Beacon Base          |
| Axis-SMB                | Intelligent Sounder Base           |
| Axis-SVMB               | Intelligent Sounder Beacon Base    |
| Axis-WP                 | Silcon Base Gasket                 |

Check if this document is up to date | Give us feedback

Advanced, The Bridges, Balliol Business Park, Newcastle, NE12 8EW, UK T: +44 (0)845 894 7000, E: enquiries@advancedco.com, W: www.advancedco.com

As our policy is one of constant product improvement the right is therefore reserved to modify product specifications without prior notice.

Version [1.00] Page 2 of 2