

Call Point

The Axis Resettable Call Point is a loop powered device designed around a fully digital protocol.

A unique manual call point that mimics the feel of breaking glass whilst offering the user the benefits and environmental advantages of a re-settable operating element.

Upon activation an indicator drops into view at the top of the window. The unit is then simply reset by use of a special key.

The same special key is used for removal of the device's front cover.

The unit provides a fast and secure response, and incorporates a bidirectional short circuit isolator.

Connections are made using plug-in terminal blocks which will accept conductors up to 2.5mm².

Key Features

- Provides high reliability and error detection
- Short circuit isolators in each device to the requirements of EN54-17
- Large capacity, up to 240 devices per loop
- Auto addressing capability (by the control panel) or manually using a hand held programmer.
- Digital checking of double address
- Line quality information
- Bicolour (red green) LED driven by the control panel

Specification

Power Supply	15-40 V
--------------	---------

Average Current Consumption	I=70 uA
-----------------------------	---------

LED Current Consumption	Iled=6mA @24Vdc
-------------------------	-----------------

Operating Temperature Range	-30°C / +70°C
-----------------------------	---------------

Humidity (non condensing)	95% RH
---------------------------	--------

Dimensions H x W x D mm	85 x 85 x 54
-------------------------	--------------

Order Codes and Options

- 20-VCP100-ADV: Red
- 20-VCP100-B- Blue
- ADV:
- 20-VCP100-G- Green
- ADV:
- 20-VCP100-Y- Yellow
- ADV:
- 20-VCP100-W- White
- ADV: