



Slave Sounder Base

The slave sounder base plus is a low profile base sounder which activates its acoustic output following the triggering of an alarm condition on the host detector. The acoustic output is selected through the dip-switch.

The sounder base is designed around a fully digital protocol and has a 240 device loop capacity. When used in conjunction with an associated intelligent detector the unit can be controlled via the cause and effect programming of an Axis EN compatible control panel.

The unit has integral DIP switches, allowing independent adjustment of both tone and volume settings. The unit's integral detector base has easy access for loop cabling and allows for the connection of both the sounder and associated detectors via a single set of cable terminations.

This sounder base is compatible with Axis-OP, Axis-OH, Axis-HT, Axis-OPX, Axis-OHX and Axis-HTX devices.


Features

- 32 programmable tones
- one and volume set via DIP switch
- Synchronised sounder
- Adjustable volume output
- Includes device identification tab
- Easy central cable entry
- Low profile design
- Ceiling mounting bracket includes sound diffuser cone, loop cables passage, pre-cut holes for screwing the bracket to the ceiling and fixing pins

Standards and Approvals

EN54-3: Fire Alarm Devices - Sounders





Specification	
Voltage range	From 16 to 40 Vdc (typical 24 Vdc)
Max current load @ 40 Vdc applied, high volume selected	2.5 mA
Max current load @ 24 Vdc applied, high volume selected	3.5 mA
Max current load @ 16 Vdc applied, high volume selected	4 mA
Acoustic output frequency range	From 440 to 2900 Hz
Maximum acoustic intensity	92.6 dB(A)
Ambient temperature range	From -10°C to +55°C
Maximum tolerated humidity	95% RH (without condensation)
IP	21C

Version [1.00] Page 1 of 2

Weight 200 g

Order Codes and Options	
Axis-S2AMB	Slave Sounder Base
Axis-OP	Intelligent Optical Smoke Detector (without isolator)
Axis-OH	Intelligent Multicriteria Detector (without isolator)
Axis-HT	Intelligent Heat Detector (without isolator)
Axis-OPX	Intelligent Optical Smoke Detector
Axis-OHX	Intelligent Multicriteria Detector
Axis-HTX	Intelligent Heat Detector

Check if this document is up to date | Give us feedback

Advanced, The Bridges, Balliol Business Park, Newcastle, NE12 8EW, UK T: +44 (0)845 894 7000, E: enquiries@advancedco.com, W: www.advancedco.com

As our policy is one of constant product improvement the right is therefore reserved to modify product specifications without prior notice.

Version [1.00] Page 2 of 2