

## Three Zone Automatic Gas Extinguishing Panel

The ExGo, three zone automatic extinguishing panel is approved to EN12094-1 (European Standard for Fixed Firefighting Systems - Components for Gas Extinguishing Systems) and EN54 - Parts 2, 4 and 13.

The ExGo system detects a fire in the same manner as a fire alarm system, but in addition to sounding alarms, it also controls the release of an extinguishing agent.

The extinguishing agent can take many forms from CO<sub>2</sub> through to specialist gases developed solely for extinguishing purposes. The agent is released into the atmosphere in the area where a fire has been detected, reducing the density of oxygen in the atmosphere around the fire, thus extinguishing the fire.

The ExGo system is used primarily in areas of significant value/strategic importance to businesses e.g. computer suites, telecom switch-rooms etc, providing a cost-effective solution to protect your work place.



### Features

- LCD display providing clearer status indication and programming routines
- Multiple languages
- Software for downloading configuration and event logs
- Passcode or optional key switch for Level 2 access
- Time and date-stamped event log and improved diagnostics
- Company logo can be displayed on LCD during normal conditions
- Large LCD/ digital countdown timer
- RS485 for remote status indicators (maximum of 7)
- PC download via USB

### Specification

Base technology	Flash-based processor
Display	Backlit 128 x 64 LCD
Remote status indicators	Supported via RS485 (maximum of 7)
Controls	Alphanumeric keypad, navigation keys and system keys for Reset, Mute, Silence/Resound and Sound alarms
Detection zones	3 x conventional detection zones (inc. support for I.S. barrier)
Extinguishing zones	1 x flooding/extinguishing zones. Support for solenoid and metron type actuators
Onboard sounder circuits	3 x 1A, 18-28vDC
Onboard relays	4 x 1A, 30vDC relay outputs (Fire, Fault & 2 x programmable)
Auxilliary supply	2 x 500mA aux supply outputs 18-28vDC (1 switched)
Programmable outputs	Support for 8 additional programmable outputs via Exp-008
Switch inputs	4 x programmable, 1 x manual trigger, 6 x release (Mode Select, Valve Monitor, Pressure Monitor, Hold, Abort, Flow)

Countdown timer	On board, large digit
Mains supply	3A universal switch mode PSU
Battery capacity	24V 7Ah
Charger current	1A
USB ports	1 x USB port for PC connection
Event log	100 fire/trigger events, 500 general log events
Enclosure, colour	Steel IP30, grey RAL7035
Cable entry	17 knockouts in enclosure top, 13 in enclosure back
Size (H x W x D)	330mm x 400mm x 95mm
Weight	6Kg

## Order Codes and Options

Ex-3001:	Extinguishing Control Panel
Exp-008F:	Programmable 8 way relay card - fitted
Exm-001:	Semi-flushing bezel for Ex-3001 panel
Exp-001:	Enable controls (trapped) key switch assembly

[Check if this document is up to date](#) | [Give us feedback](#)

Advanced, The Bridges, Balliol Business Park, Newcastle, NE12 8EW, UK **T:** +44 (0)845 894 7000, **E:** [enquiries@advancedco.com](mailto:enquiries@advancedco.com), **W:** [www.advancedco.com](http://www.advancedco.com)

As our policy is one of constant product improvement the right is therefore reserved to modify product specifications without prior notice.