







FLX series Comparison Chart


Part Number
FLX-S series
FLX-P series
FLX-A series
Detection


Part Number	FLX-S-ST	FLX-S-DT	FLX-P-ST	FLX-P-DT	FLX-A-AM	FLX-A-DAM
Detection Method	Passive Infrared	Passive infrared with Tough Mod 2 microwave	Passive Infrared	Passive infrared with Tough Mod 2 microwave	Passive Infrared	Passive infrared with Tough Mod 2 microwave
Certificate	EN-50131-2-2	EN-50131-2-4	EN-50131-2-2	EN-50131-2-4	EN-50131-2-2	EN-50131-2-4
Grading	2		2		3	
Detection range	12m x 12m (85°) or 18m x 2m (5°)		15m x 15m (85°) or 24m x 2m (5°)		15m x 15m (85°) or 24m x 2m (5°)	
Installation height	2.0m > 3.0m		2.0m > 3.0m		2.0m > 3.0m	
SMDA Digital Logic						
Human Capture Element						
Pet Tolerance						
Double conductive shielding						
PEU socket						
Anti-masking						
Super High Sensitivity						
EOL Resistor Socket						
Cartridge system						
Dual Anti-masking						
Down Zone Switch						
Wall / Ceiling bracket	CW-G2		CW-G2		CW-G3	

Dimensions


Unit: mm (inch)