WISENET WAVE



WRN-810S

Wisenet WAVE 1U PoE+ NVR (minimum 4 channels license included)

Benefits

- Designed to provide a cost-effective way for users to take advantage of the highly popular Wisenet WAVE video management software (VMS)
- Ready to be used out-of-the-box with no need for an installer
- Preloaded with 4 WAVE Professional licenses to ensure quick and easy deployment with minimum setup time
- Built-in PoE switch provides an installation time saving method of supplying power to connected cameras
- Wisenet WAVE features an intuitive 'drag & drop' tool which makes it extremely easy for operators to set up a display of live and recorded images on a single screen or video wall
- A wide range of Smart search options, including keyword, calendar and time-slice search, enable operators to quickly retrieve recorded video of specific incidents

		WRN-8105
DISPLAY		
Video	Innute	
Live	Inputs Local Display	Up to 8CH 1x HDMI, 1x VGA dual monitor
PERFORMANCE	Local Display	
Operating System	Embedded	Linux Ubuntu Wisenet WAVE
Video Management Software	Empedded	
Recording	Recording Bandwidth	Up to 80 Mbps
Storage	Built-in OS	1x eMMC SSD (embedded)
	Internal HDD	2 SATA (Max. 12TB)
Sensor	Input/Output	4/2
NETWORK		
Interface		2 x RJ-45, Gigabit Ethernet, 8 x PoE+ 100Mbps
FUNCTIONS		
System Control		Mouse, Keyboard
INDICATOR/INTERFACE		
Front	Indicator	Power status LED 1ea, HDD action LED 1ea, Alarm status LED 1ea Record status LED 1ea, PoE over Budget LED 1ea, Network action LED 1ea
	USB	3ea (Front x2, Rear x1)
Connections	Audio	Stereo Jack (Left-Right)
	HDMI / VGA	HDMI : Up to 4K (3840 x 2160), VGA : Max. 1080p
	Ethernet	8ea (PoE (PoE+), 100Mbps), 2ea (LAN/WAN, 1Gbps)
GENERAL		
ENVIRONMENTAL		
	Operating Temperature	+0°C to +40°C (+32°F to +104°F)
	Operating Humidity	20% ~ 85% RH
ELECTRICAL		
	Input Voltage / Current	100 ~ 240V AC
	Power Consumption	Max. 164 W (2 HDDs, PoE(PoE+) on), Max. 37 W (2 HDDs, PoE(PoE+) off)
	PoE Budget	Each Max. 30 W (0.55 A), Total Max. 100 W (1.85 A)
MECHANICAL		
	Form Factor	1U rack mount chassis
	Colour / Material	Black / Metal
	Dimension (WxHxD)	370 x 50.7 x 324.3 mm (14.57″ x 2″ x 12.77″)
	Weight	2.7 kg (without HDDs)

* The latest product information / specification can be found at hanwha-security.com

* Design and specifications are subject to change without notice.

* Wisenet is the proprietary brand of Hanwha Techwin.



WISENET WAVE

Key Features

- Preloaded and configured with Wisenet WAVE video management system
- Includes WAVE Professional Licenses
- · Supported by Wave client, mobile and Cloud Sync
- Supports AI metadata
- 80 Mbps of recording throughput
- Supports up to 12TB internal storage
- HDMI/VGA monitor outputs for configuration and basic monitoring
- 8 PoE/PoE+ ports, with a total power budget of 100W, 2 Gigabit uplink ports
- PoE port control & Alarm I/O supported
- ONVIF camera compliant
- 1U Rack mountable
- · Recommended maximum of 30 servers for a merged system
- Includes USB mouse and rack mount brackets

Dimensions

Unit:mm(inch)







